Quality Assurance
Site Survey Report for SA Recycling

Last updated May, 2017

AQS ID	ARB Number	Site Start Date	Reporting Agency and Agency Code
060711407	70046	6/2012	South Coast AQMD (061)

Site Address	County	Air Basin	Latitude	Longitude	Elevation
8822 Etiwanda Ave. , Rancho Cucamonga,CA,91739	San Bernardino	South Coast	34° 05' 35"N	117° 31' 41"W	351 m


Topo Map
Day
East
Water Tanks
ARROW
ROUTE
AVE
PEGAN AVE
ILEX
WHITTRAM
Etiwanda
(Siding)
WT
SANTA FE
Rochester
Powerplant
Water Tank
MWD
UPPER
FEEDER
1180
1170
1159
1154
1150
1130
1100

Detailed Site Information

Local site name	SA Recycling
AQS ID	Unavailable
GPS coordinates (decimal degrees)	Latitude: 34° 05' 35"N Longitude: 117° 31' 41"W
Street Address	8822 Etiwanda Ave. , Rancho Cucamonga,CA,91739
County	San Bernardino
Distance to roadways (meters)	400 m
Traffic count (AADT, year)	Unavailable
Groundcover (e.g. asphalt, dirt, sand)	Asphalt
Representative statistical area name (i.e. MSA, CBSA, other)	40140-Riverside-San Bernardino-Ontario, CA MSA

Pollutant, POC	Lead, 1	Metals, CR6, 1		
Primary / QA Collocated / Other	N/A	Primary		
Parameter code	14129	See Table 26		
Basic monitoring objective(s)	NAAQS	NAAQS		
Site type(s)	Source Oriented	Source Oriented		
Monitor (type)	SLAMS	SLAMS		
Network affiliation	Microscale Pb	NATTS		
Instrument manufacturer and model	GMW 1200 TSP	RM Env. 924, A Sampler		
Method code	110	See Table 26		
FRM/FEM/ARM/ other	FRM	Other		
Collecting Agency	SCAQMD	SCAQMD		
Analytical Lab (i.e.weigh lab, toxics lab, other)	SCAQMD	SCAQMD		
Reporting Agency	SCAQMD	SCAQMD		
Spatial scale (e.g. micro, neighborhood)	Micro	Micro		
Monitoring start date (MM/DD/YYYY)	6/26/12	7/19/12		
Current sampling frequency (e.g.1:3, continuous)	1:6	1:3		
Calculated sampling frequency (e.g. 1:3/1:1)	1:6	No CFR mandated sampling schedule.		
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31		
Probe height (meters)	2.6	3		
Distance from supporting structure (meters)	1	1.6		
Distance from obstructions on roof (meters)	N/A	N/A		

Distance from obstructions not on roof (meters)	N/A	N/A		
Distance from trees (meters)	N/A	N/A		
Distance to furnace or incinerator flue (meters)	N/A	N/A		
Distance between collocated monitors (meters)	N/A	N/A		
Unrestricted airflow (degrees)	360°	360°		
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A		
Residence time for reactive gases (seconds)	N/A	N/A		
Will there be changes within the next 18 months? (Y/N)	No	No		
Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A		
Frequency of flow rate verification for manual PM samplers	Monthly	Monthly		
Frequency of flow rate verification for automated PM analyzers	N/A	N/A		
Frequency of one-point QC check for gaseous instruments	N/A	N/A		
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A		
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	05/13/2016, 11/22/2016	N/A		